

75kg

Design Casters Series LEVINA


Housing and wheels made from high grade synthetic materials with integrated threadguards, fittings blue passivated, Color: silver-grey RAL 7001. The caster meets all requirements for EN 12530, except for swivel play. Load capacity tested according EN 12530



Swivel Casters	Wheel diameter [mm]	Tread width [mm]	Center hole [mm]	Swivel Radius [mm]	Overall height [mm]	Load capacity [kg]	Order number
	75	25	10	64.5	103	75	5320PJO075L51-10



Swivel Casters with wheel brake	Wheel diameter [mm]	Tread width [mm]	Center hole [mm]	Swivel Radius [mm]	Overall height [mm]	Load capacity [kg]	Order number
	75	25	10	73	103	75	5325PJO075L51-10



<p>Wheel: PJO Wheel center: Polypropylene, Tread: TENTEprene (thermoplastic rubber), without threadguards, plain bearing</p>	<p>Grey Brake Pedal These casters are available with grey locking lever.</p>	<p>Fittings Matching fittings can be found on page 189.</p>
---	---	--



75kg Design Casters Series LEVINA

Housing and wheels made from high grade synthetic materials with integrated threadguards, fittings blue passivated, Color: silver-grey RAL 7001. The caster meets all requirements for EN 12530, except for swivel play. Load capacity tested according EN 12530



Swivel Casters







Wheel diameter [mm]	Tread width [mm]	Center hole [mm]	Swivel Radius [mm]	Overall height [mm]	Load capacity [kg]	Order number
75	25	10	64.5	103	75	5320PJP075L51-10

Swivel Casters with wheel brake



Wheel diameter [mm]	Tread width [mm]	Center hole [mm]	Swivel Radius [mm]	Overall height [mm]	Load capacity [kg]	Order number
75	25	10	73	103	75	5325PJP075L51-10



 <p>Wheel: PJP Wheel center: Polypropylene, Tread: TENTEprene (thermoplastic rubber), with integrated threadguards, precision ball bearing</p>	 <p>Grey Brake Pedal These casters are available with grey locking lever.</p>	 <p>Fittings Matching fittings can be found on page 189.</p>
--	---	--

75kg

Design Casters Series LEVINA

Housing and wheels made from high grade synthetic materials with integrated threadguards, fittings blue passivated, Color: silver-grey RAL 7001. The caster meets all requirements for EN 12530, except for swivel play. Load capacity tested according EN 12530



Swivel Casters									Order number
	75	25	77 x 67	61,5/56 x 51,5/46,5	8,5	27	103	75	5320PJO075P50
	75	25	95 x 70	52/44.45 x 76/72	11	27	103	75	5320PJO075P52

Swivel Casters with wheel brake									Order number
	75	25	77 x 67	61,5/56 x 51,5/46,5		27	103	75	5325PJO075P50
	75	25	95 x 70	52/44.45 x 76/72	11	27	103	75	5325PJO075P52

<p>Wheels: PJO Wheel center: Polypropylene, Tread: TENTEprene (thermoplastic rubber), without threadguards, plain bearing</p>	<p>Grey Brake Pedal These casters are available with grey locking lever.</p>	<p>Fittings Matching fittings can be found on page 189.</p>
--	---	--






75kg Design Casters Series LEVINA

Housing and wheels made from high grade synthetic materials with integrated threadguards, fittings blue passivated, Color: silver-grey RAL 7001. The caster meets all requirements for EN 12530, except for swivel play. Load capacity tested according EN 12530



Swivel Casters									Order number
	75	25	77 x 67	61,5/56 x 51,5/46,5	8,5	27	103	75	5320PJP075P50
	75	25	95 x 70	52/44.45 x 76/72	11	27	103	75	5320PJP075P52

Swivel Casters with wheel brake									Order number
	75	25	77 x 67	61,5/56 x 51,5/46,5	8,5	27	103	75	5325PJP075P50
	75	25	95 x 70	52/44.45 x 76/72	11	27	103	75	5325PJP075P52

 <p>Wheels: PJP Wheel center: Polypropylene, Tread: TENTEprene (thermoplastic rubber), with integrated threadguards, precision ball bearing</p>	 <p>Grey Brake Pedal These casters are available with grey locking lever.</p>	 <p>Fittings Matching fittings can be found on page 189.</p>
---	---	--

75kg

Design Casters Series LEVINA

Housing and wheels made from high grade synthetic materials with integrated threadguards, fittings blue passivated, Color: silver-grey RAL 7001. The caster meets all requirements for EN 12530, except for swivel play. Load capacity tested according EN 12530



Swivel Casters										Order number
	75	25	9.4 x 25			27	103	75		5320PJO075S70-9.4x25
	75	25	12.4 x 25			27	103	75		5320PJO075S70-12.4x25

Swivel Casters with wheel brake										Order number
	75	25	9.4 x 25			27	103	75		5325PJO075S70-9.4x25
	75	25	12.4 x 25			27	103	75		5325PJO075S70-12.4x25

<p>Wheels: PJO Wheel center: Polypropylene, Tread: TENTEprene (thermoplastic rubber), without threadguards, plain bearing</p>	<p>Grey Brake Pedal These casters are available with grey locking lever.</p>	<p>Fittings Matching fittings can be found on page 189.</p>
--	---	--



75kg


Design Casters Series LEVINA

Housing and wheels made from high grade synthetic materials with integrated threadguards, fittings blue passivated, Color: silver-grey RAL 7001. The caster meets all requirements for EN 12530, except for swivel play. Load capacity tested according EN 12530






Swivel Casters	Wheel diameter [mm]	Tread width [mm]	Threaded stem [mm]			Offset [mm]	Overall height [mm]	Load capacity [kg]	Order number
	75	25	9.4 x 25			27	103	75	5320PJP075S70-9.4x25
	75	25	12.4 x 25			27	103	75	5320PJP075S70-12.4x25



Swivel Casters with wheel brake	Wheel diameter [mm]	Tread width [mm]	Threaded stem [mm]			Offset [mm]	Overall height [mm]	Load capacity [kg]	Order number
	75	25	9.4 x 25			27	103	75	5325PJP075S70-9.4x25
	75	25	12.4 x 25			27	103	75	5325PJP075S70-12.4x25



 <p>Wheels: PJP Wheel center: Polypropylene, Tread: TENTEprene (thermoplastic rubber), with integrated threadguards, precision ball bearing</p>	 <p>Grey Brake Pedal These casters are available with grey locking lever.</p>	 <p>Fittings Matching fittings can be found on page 189.</p>
---	---	--

100kg

Design Casters Series LEVINA

Housing and wheels made from high grade synthetic materials with integrated threadguards, fittings double ball bearing swivel head, all fittings bright zinc plated, blue passivated.


Color: silver-grey RAL 7001

Drawings of plate fittings see page 42 - 43.

Load capacity tested according EN 12530



	Wheel diameter [mm]	Tread width [mm]	Plate size [mm]	Plate hole centers [mm]	Plate hole [mm]	Offset [mm]	Overall height [mm]	Load capacity [kg]		Order number
Swivel Casters										
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5370PJP100P50
	100	32	95 x 70	52/44.45 x 76/72	10	36	137	100		5370PJP100P52
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	100		5370PJP125P50
	125	32	95 x 70	52/44.45 x 76/72	11	38	165	100		5370PJP125P52
	150	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	190	100		5370PJP150P50
	150	32	77 x 67	52/44.45 x 76/72	11	38	190	100		5370PJP150P52
Swivel Casters with total lock										Order number
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5377PJP100P50
	100	32	95 x 70	52/44.45 x 76/72	11	36	137	100		5377PJP100P52
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	100		5377PJP125P50
	125	32	95 x 70	52/44.45 x 76/72	11	38	165	100		5377PJP125P52
	150	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	190	100		5377PJP150P50
	150	32	95 x 70	52/44.45 x 76/72	11	38	194	100		5377PJP150P52
Swivel Casters with directional lock										Order number
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5371PJP100P50
	100	32	95 x 70	52/44.45 x 76/72	11	36	137	100		5371PJP100P52
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	100		5371PJP125P50
	125	32	95 x 70	52/44.45 x 76/72	11	38	161	100		5371PJP125P52
	150	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	190	100		5371PJP150P50
	150	32	95 x 70	52/44.45 x 76/72	11	38	190	100		5371PJP150P52



Wheel: PJP
Wheel center: Polypropylene, Tread: TENTEprene (thermoplastic rubber), with integrated threadguards, precision ball bearing



Color options
All versions available in "grey-white RAL 9002" and "graphite-black RAL 9011".



Grey brake pedal
These casters are available with grey locking lever.



LEVINA XL
In wheel diameter 125 mm these casters are also available with extended fork for a better access to the brake pedal.



100kg Design Casters Series LEVINA

Housing and wheels made from high grade synthetic materials with integrated threadguards, fittings blue passivated, Color: silver-grey RAL 7001
Load capacity tested according EN 12530



Swivel Casters	Wheel diameter [mm]	Tread width [mm]	Center hole [mm]	Offset [mm]	Overall height [mm]	Load capacity [kg]	Order number
	100	32	11	36	137	100	5370PJP100P30-11
	100	32	13	36	137	100	5370PJP100P30-13
	125	32	11	38	161	100	5370PJP125P30-11
	125	32	13	38	161	100	5370PJP125P30-13
	150	32	11	38	190	100	5370PJP150P30-11
	150	32	13	38	190	100	5370PJP150P30-13

Swivel Casters with total lock	Wheel diameter [mm]	Tread width [mm]	Center hole [mm]	Offset [mm]	Overall height [mm]	Load capacity [kg]	Order number
	100	32	11	36	137	100	5377PJP100P30-11
	100	32	13	36	137	100	5377PJP100P30-13
	125	32	11	38	161	100	5377PJP125P30-11
	125	32	13	38	161	100	5377PJP125P30-13
	150	32	11	38	190	100	5377PJP150P30-11
	150	32	13	38	190	100	5377PJP150P30-13

Swivel Casters with directional lock	Wheel diameter [mm]	Tread width [mm]	Center hole [mm]	Offset [mm]	Overall height [mm]	Load capacity [kg]	Order number
	100	32	11	36	137	100	5371PJP100P30-11
	100	32	13	36	137	100	5371PJP100P30-13
	125	32	11	38	161	100	5371PJP125P30-11
	125	32	13	38	161	100	5371PJP125P30-13
	150	32	11	38	190	100	5371PJP150P30-11
	150	32	13	38	190	100	5371PJP150P30-13

Wheel: PJP
Wheel center: Polypropylene, Tread: TENTEprene (thermoplastic rubber), with integrated threadguards, precision ball bearing

Grey brake pedal
These casters are available with grey locking lever.

Buffer wheel
These casters are available with assembled buffer wheel. For further assistance please contact us.

LEVINA XL
In wheel diameter 125 mm these casters are also available with extended fork for a better access to the brake pedal.

100kg


Design Casters Series LEVINA

Housing and wheels made from high grade synthetic materials with integrated threadguards, fittings blue passivated,
Color: silver-grey RAL 7001

Load capacity tested according EN 12530



	Wheel diameter [mm]	Tread width [mm]	Bolt-Ø [mm]	Bolt length [mm]	Offset [mm]	Overall height [mm]	Load capacity [kg]		
Swivel Casters								Order number	
	100	32	22	45	36	137	100	5370PJP100R05-22x45	
	100	32	25.4	45	36	137	100	5370PJP100R05-25.4	
	100	32	28	45	36	137	100	5370PJP100R05-28x45	
	125	32	22	45	38	161	100	5370PJP125R05-22x45	
	125	32	25.4	45	38	161	100	5370PJP125R05-25.4	
	125	32	28	45	38	161	100	5370PJP125R05-28x45	
	150	32	22	45	38	190	100	5370PJP150R05-22x45	
	150	32	25.4	45	38	190	100	5370PJP150R05-25.4	
	150	32	28	45	38	190	100	5370PJP150R05-28x45	
Swivel Casters with total lock								Order number	
	100	32	22	45	36	137	100	5377PJP100R05-22x45	
	100	32	25.4	45	36	137	100	5377PJP100R05-25.4	
	100	32	28	45	36	137	100	5377PJP100R05-28x45	
	125	32	22	45	38	161	100	5377PJP125R05-22x45	
	125	32	25.4	45	38	161	100	5377PJP125R05-25.4	
	125	32	28	45	38	161	100	5377PJP125R05-28x45	
	150	32	22	45	38	190	100	5377PJP150R05-22x45	
	150	32	25.4	45	38	190	100	5377PJP150R05-25.4	
	150	32	28	45	38	190	100	5377PJP150R05-28x45	
Swivel Casters with directional lock								Order number	
	100	32	22	45	36	137	100	5371PJP100R05-22x45	
	100	32	25.4	45	36	137	100	5371PJP100R05-25.4	
	100	32	28	45	36	137	100	5371PJP100R05-28x45	
	125	32	22	45	38	161	100	5371PJP125R05-22x45	
	125	32	25.4	45	38	161	100	5371PJP125R05-25.4	
	125	32	28	45	38	161	100	5371PJP125R05-28x45	
	150	32	22	45	38	190	100	5371PJP150R05-22x45	
	150	32	25.4	45	38	190	100	5371PJP150R05-25.4	
	150	32	28	45	38	190	100	5371PJP150R05-28x45	


Wheel: PJP

Wheel center: Polypropylene, Tread: TENTEprene (thermoplastic rubber), with integrated threadguards, precision ball bearing


Grey brake pedal

These casters are available with grey locking lever.


LEVINA XL

In wheel diameter 125 mm these casters are also available with extended fork for a better access to the brake pedal.



80 - 100kg

Design Casters Series LEVINA

Housing and wheels made from high grade synthetic materials with integrated threadguards, fittings double ball bearing swivel head, all fittings bright zinc plated, blue passivated.


Color: silver-grey RAL 7001

Drawings of plate fittings see page 42 - 43.

Load capacity tested according EN 12530



	Wheel diameter [mm]	Tread width [mm]	Plate size [mm]	Plate hole centers [mm]	Plate hole [mm]	Offset [mm]	Overall height [mm]	Load capacity [kg]		Order number
Swivel Casters										
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5370UAP100P50
	100	32	95 x 70	52/44.45 x 76/72	11	36	141	100		5370UAP100P52
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5370XSP100P50
	100	32	95 x 70	52/44.45 x 76/72	11	36	141	100		5370XSP100P52
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	100		5370UAP125P50
	125	32	95 x 70	52/44.45 x 76/72	11	38	165	100		5370UAP125P52
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	80		5370XSP125P50
	125	32	95 x 70	52/44.45 x 76/72	11	38	165	100		5370XSP125P52
	150	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	190	100		5370UAP150P50
	150	32	95 x 70	52/44.45 x 76/72	11	38	194	100		5370UAP150P52
Swivel Casters with total lock										
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5377UAP100P50
	100	32	95 x 70	52/44.45 x 76/72	11	36	141	100		5377UAP100P52
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5377XSP100P50
	100	32	95 x 70	52/44.45 x 76/72	11	36	141	100		5377XSP100P52
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	100		5377UAP125P50
	125	32	95 x 70	52/44.45 x 76/72	11	38	165	100		5377UAP125P52
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	80		5377XSP125P50
	125	32	95 x 70	52/44.45 x 76/72	11	38	165	100		5377XSP125P52
	150	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	190	100		5377UAP150P50
	150	32	95 x 70	52/44.45 x 76/72	11	38	194	100		5377UAP150P52
Swivel Casters with directional lock										
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5371UAP100P50
	100	32	95 x 70	52/44.45 x 76/72	11	36	141	100		5371UAP100P52
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5371XSP100P50
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	100		5371UAP125P50
	125	32	95 x 70	52/44.45 x 76/72	11	38	165	100		5371UAP125P52
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	80		5371XSP125P50
	125	32	95 x 70	52/44.45 x 76/72	11	38	165	100		5371XSP125P52
	150	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	190	100		5371UAP150P50
	150	32	95 x 70	52/44.45 x 76/72	11	38	194	100		5371UAP150P52



Wheel: UAP
Wheel center: Polyamide, Tread: Polyurethane, with integrated threadguards, precision ball bearing

Wheel: XSP electric conductive, non-marking
Wheel center: Polyamide, Tread: Polyurethane, with integrated threadguards, precision ball bearing

Grey brake pedal
These casters are available with grey locking lever.

LEVINA XL
In wheel diameter 125 mm these casters are also available with extended fork for a better access to the brake pedal.

80 - 100kg

Design Casters Series LEVINA

Housing and wheels made from high grade synthetic materials with integrated threadguards, fittings blue passivated,
Color: silver-grey RAL 7001

Load capacity tested according EN 12530



	Wheel diameter [mm]	Tread width [mm]	Center hole [mm]			Offset [mm]	Overall height [mm]	Load capacity [kg]		Order number
Swivel Casters										
	100	32	11			36	137	100		5370UAP100P30-11
	100	32	13			36	137	100		5370UAP100P30-13
	100	32	11			36	137	100		5370XSP100P30-11
	100	32	13			36	137	100		5370XSP100P30-13
	125	32	11			38	161	100		5370UAP125P30-11
	125	32	13			38	161	100		5370UAP125P30-13
	125	32	11			38	161	80		5370XSP125P30-11
	125	32	13			38	161	80		5370XSP125P30-13
	150	32	11			38	190	100		5370UAP150P30-11
	150	32	13			38	190	100		5370UAP150P30-13
Swivel Casters with total lock										Order number
	100	32	11			36	137	100		5377UAP100P30-11
	100	32	13			36	137	100		5377UAP100P30-13
	100	32	11			36	137	100		5377XSP100P30-11
	100	32	13			36	137	100		5377XSP100P30-13
	125	32	11			38	161	100		5377UAP125P30-11
	125	32	13			38	161	100		5377UAP125P30-13
	125	32	11			38	161	80		5377XSP125P30-11
	125	32	13			38	161	80		5377XSP125P30-13
	150	32	11			38	190	100		5377UAP150P30-11
	150	32	13			38	190	100		5377UAP150P30-13
Swivel Casters with directional lock										Order number
	100	32	11			36	137	100		5371UAP100P30-11
	100	32	13			36	137	100		5371UAP100P30-13
	100	32	11			36	137	100		5371XSP100P30-11
	100	32	13			36	137	100		5371XSP100P30-13
	125	32	11			38	161	100		5371UAP125P30-11
	125	32	13			38	161	100		5371UAP125P30-13
	125	32	11			38	161	80		5371XSP125P30-11
	125	32	13			38	161	80		5371XSP125P30-13
	150	32	11			38	190	100		5371UAP150P30-11
	150	32	13			38	190	100		5371UAP150P30-13



Wheel: UAP
Wheel center: Polyamide, Tread: Polyurethane, with integrated threadguards, precision ball bearing



Wheel: XSP electric conductive, non-marking
Wheel center: Polyamide, Tread: Polyurethane, with integrated threadguards, precision ball bearing



Grey brake pedal
These casters are available with grey locking lever.



LEVINA XL
In wheel diameter 125 mm these casters are also available with extended fork for a better access to the brake pedal.




80 - 100kg

Design Casters Series LEVINA

Housing and wheels made from high grade synthetic materials with integrated threadguards, fittings blue passivated, Color: silver-grey RAL 7001
Load capacity tested according EN 12530



	Wheel diameter [mm]	Tread width [mm]	Bolt-Ø [mm]	Bolt length [mm]	Offset [mm]	Overall height [mm]	Load capacity [kg]		Order number
Swivel Casters									
	100	32	25.4	45	36	137	100		5370UAP100R05-25.4
	100	32	25.4	45	36	137	100		5370XSP100R05-25.4
	100	32	28	45	36	137	100		5370UAP100R05-28x45
	100	32	28	45	36	137	100		5370XSP100R05-28x45
	125	32	25.4	45	38	161	100		5370UAP125R05-25.4
	125	32	28	45	38	161	100		5370UAP125R05-28x45
	125	32	25.4	45	38	161	100		5370XSP125R05-25.4
	125	32	28	45	38	161	80		5370XSP125R05-28x45
	150	32	25.4	45	38	190	100		5370UAP150R05-25.4
	150	32	28	45	38	190	100		5370UAP150R05-28x45
Swivel Casters with total lock									
	100	32	25.4	45	36	137	100		5377UAP100R05-25.4
	100	32	28	45	36	137	100		5377UAP100R05-28x45
	100	32	25.4	45	36	137	100		5377XSP100R05-25.4
	100	32	28	45	36	137	100		5377XSP100R05-28x45
	125	32	25.4	45	38	161	100		5377UAP125R05-25.4
	125	32	28	45	38	161	100		5377UAP125R05-28x45
	125	32	25.4	45	38	161	100		5377XSP125R05-25.4
	125	32	28	45	38	161	80		5377XSP125R05-28x45
	150	32	25.4	45	38	190	100		5377UAP150R05-25.4
	150	32	28	45	38	190	100		5377UAP150R05-28x45
Swivel Casters with directional lock									
	100	32	25.4	45	36	137	100		5371UAP100R05-25.4
	100	32	28	45	36	137	100		5371UAP100R05-28x45
	100	32	25.4	45	36	137	100		5371XSP100R05-25.4
	100	32	28	45	36	137	100		5371XSP100R05-28x45
	125	32	25.4	45	38	161	100		5371UAP125R05-25.4
	125	32	28	45	38	161	100		5371UAP125R05-28x45
	125	32	25.4	45	38	161	100		5371XSP125R05-25.4
	125	32	28	45	38	161	80		5371XSP125R05-28x45
	150	32	25.4	45	38	190	100		5371UAP150R05-25.4
	150	32	28	45	38	190	100		5371UAP150R05-28x45



Fitting Options: also available with R05-22 solid stem. Matching adapters can be found on page 196

<p>Wheel: UAP Wheel center: Polyamide, Tread: Polyurethane, with integrated threadguards, precision ball bearing</p>	<p>Wheel: XSP electric conductive, non-marking Wheel center: Polyamide, Tread: Polyurethane, with integrated threadguards, precision ball bearing</p>	<p>Grey brake pedal These casters are available with grey locking lever.</p>	<p>LEVINA XL In wheel diameter 125 mm these casters are also available with extended fork for a better access to the brake pedal.</p>
---	--	---	--

100kg

Design Casters Series LEVINA stainless

Housing and wheels made from high grade synthetic materials with integrated threadguards, double ball bearing swivel head, all metal components stainless steel,


Color: silver-grey RAL 7001

Drawings of plate fittings see page 42 - 43.

Load capacity tested according EN 12530



	Wheel diameter [mm]	Tread width [mm]	Plate size [mm]	Plate hole centers [mm]	Plate hole [mm]	Offset [mm]	Overall height [mm]	Load capacity [kg]		Order number
Swivel Casters										
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5380PJC100P50
	100	32	95 x 70	52/44.45 x 76/72	11	36	141	100		5380PJC100P52
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	100		5380PJC125P50
	125	32	95 x 70	52/44.45 x 76/72	11	38	165	100		5380PJC125P52
	150	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	190	100		5380PJC150P50
	150	32	95 x 70	52/44.45 x 76/72	11	38	194	100		5380PJC150P52
Swivel Casters with total lock										Order number
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5387PJC100P50
	100	32	95 x 70	52/44.45 x 76/72	11	36	141	100		5387PJC100P52
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	100		5387PJC125P50
	125	32	95 x 70	52/44.45 x 76/72	11	38	165	100		5387PJC125P52
	150	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	190	100		5387PJC150P50
	150	32	95 x 70	52/44.45 x 76/72	11	38	194	100		5387PJC150P52
Swivel Casters with directional lock										Order number
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5381PJC100P50
	100	32	95 x 70	52/44.45 x 76/72	11	36	141	100		5381PJC100P52
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	100		5381PJC125P50
	125	32	95 x 70	52/44.45 x 76/72	11	38	165	100		5381PJC125P52
	150	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	190	100		5381PJC150P50
	150	32	95 x 70	52/44.45 x 76/72	11	38	194	100		5381PJC150P52


Wheel: PJC

Wheel center: Polypropylene, Tread: TENTEprene (thermoplastic rubber), with integrated threadguards, precision ball bearing, stainless


Color options

All versions available in "grey-white RAL 9002" and "graphite-black RAL 9011".


Grey brake pedal

These casters are available with grey locking lever.


LEVINA XL

In wheel diameter 125 mm these casters are also available with extended fork for a better access to the brake pedal.



100kg



Design Casters Series LEVINA stainless

Housing and wheels made from high grade synthetic materials with integrated threadguards, double ball bearing swivel head, all metal components stainless steel,
Color: silver-grey RAL 7001





Load capacity tested according EN 12530



Swivel Casters	Wheel diameter [mm]	Tread width [mm]	Center hole [mm]	Offset [mm]	Overall height [mm]	Load capacity [kg]	Order number
	100	32	11	36	137	100	5380PJC100P30-11
	100	32	13	36	137	100	5380PJC100P30-13
	125	32	11	38	161	100	5380PJC125P30-11
	125	32	13	38	161	100	5380PJC125P30-13
	150	32	11	38	190	100	5380PJC150P30-11
	150	32	13	38	190	100	5380PJC150P30-13

Swivel Casters with total lock	Wheel diameter [mm]	Tread width [mm]	Center hole [mm]	Offset [mm]	Overall height [mm]	Load capacity [kg]	Order number
	100	32	11	36	137	100	5387PJC100P30-11
	100	32	13	36	137	100	5387PJC100P30-13
	125	32	11	38	161	100	5387PJC125P30-11
	125	32	13	38	161	100	5387PJC125P30-13
	150	32	11	38	190	100	5387PJC150P30-11
	150	32	13	38	190	100	5387PJC150P30-13

Swivel Casters with directional lock	Wheel diameter [mm]	Tread width [mm]	Center hole [mm]	Offset [mm]	Overall height [mm]	Load capacity [kg]	Order number
	100	32	11	36	137	100	5381PJC100P30-11
	100	32	13	36	137	100	5381PJC100P30-13
	125	32	11	38	161	100	5381PJC125P30-11
	125	32	13	38	161	100	5381PJC125P30-13
	150	32	11	38	190	100	5381PJC150P30-11
	150	32	13	38	190	100	5381PJC150P30-13

 <p>Wheel: PJC Wheel center: Polypropylene, Tread: TENTEprene (thermoplastic rubber), with integrated threadguards, precision ball bearing, stainless</p>	 <p>Grey brake pedal These casters are available with grey locking lever.</p>	 <p>Buffer wheel These casters are available with assembled buffer wheel. For further assistance please contact us.</p>	 <p>LEVINA XL In wheel diameter 125 mm these casters are also available with extended fork for a better access to the brake pedal.</p>
---	---	---	--

100kg



Design Casters Series LEVINA stainless

Housing and wheels made from high grade synthetic materials with integrated threadguards, double ball bearing swivel head, all metal components stainless steel,

Color: silver-grey RAL 7001


Load capacity tested according EN 12530



Swivel Casters



Wheel diameter [mm]	Tread width [mm]	Bolt-Ø [mm]	Bolt length [mm]	Offset [mm]	Overall height [mm]	Load capacity [kg]
100	32	25.4	45	36	137	100
100	32	28	45	36	137	100
125	32	25.4	45	38	161	100
125	32	28	45	38	161	100
150	32	25.4	45	38	190	100
150	32	28	45	38	190	100



Order number
5380PJC100R05-25.4
5380PJC100R05-28x45
5380PJC125R05-25.4
5380PJC125R05-28x45
5380PJC150R05-25.4
5380PJC150R05-28x45

Swivel Casters with total lock



Wheel diameter [mm]	Tread width [mm]	Bolt-Ø [mm]	Bolt length [mm]	Offset [mm]	Overall height [mm]	Load capacity [kg]
100	32	25.4	45	36	137	100
100	32	28	45	36	137	100
125	32	25.4	45	38	161	100
125	32	28	45	38	161	100
150	32	25.4	45	38	190	100
150	32	28	45	38	190	100

Order number
5387PJC100R05-25.4
5387PJC100R05-28x45
5387PJC125R05-25.4
5387PJC125R05-28x45
5387PJC150R05-25.4
5387PJC150R05-28x45

Swivel Casters with directional lock



Wheel diameter [mm]	Tread width [mm]	Bolt-Ø [mm]	Bolt length [mm]	Offset [mm]	Overall height [mm]	Load capacity [kg]
100	32	25.4	45	36	137	100
100	32	28	45	36	137	100
125	32	25.4	45	38	161	100
125	32	28	45	38	161	100
150	32	25.4	45	38	190	100
150	32	28	45	38	190	100

Order number
5381PJC100R05-25.4
5381PJC100R05-28x45
5381PJC125R05-25.4
5381PJC125R05-28x45
5381PJC150R05-25.4
5381PJC150R05-28x45



Wheel: PJC
Wheel center: Polypropylene, Tread: TENTEprene (thermoplastic rubber), with integrated threadguards, precision ball bearing, stainless



Grey brake pedal
These casters are available with grey locking lever.



LEVINA XL
In wheel diameter 125 mm these casters are also available with extended fork for a better access to the brake pedal.



Fitting Option:
Also available with R05-22mm solid stem.



80 - 100kg



Design Casters Series LEVINA stainless

Housing and wheels made from high grade synthetic materials with integrated threadguards, double ball bearing swivel head, all metal components stainless steel,


Color: silver-grey RAL 7001

Drawings of plate fittings see pages 42 - 43.

Load capacity tested according EN 12530



	Wheel diameter [mm]	Tread width [mm]	Plate size [mm]	Plate hole centers [mm]	Plate hole [mm]	Offset [mm]	Overall height [mm]	Load capacity [kg]		Order number
Swivel Casters										
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5380UAC100P50
	100	32	95 x 70	52/44.5 x 76/72	11	36	141	100		5380UAC100P52
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5380XSC100P50
	100	32	95 x 70	52/44.5 x 76/72	11	36	141	100		5380XSC100P52
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	100		5380UAC125P50
	125	32	95 x 70	52/44.5 x 76/72	11	38	165	100		5380UAC125P52
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	80		5380XSC125P50
	125	32	95 x 70	52/44.5 x 76/72	11	38	165	100		5380XSC125P52
	150	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	190	100		5380UAC150P50
	150	32	95 x 70	52/44.5 x 76/72	11	38	194	100		5380UAC150P52
Swivel Casters with total lock										
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5387UAC100P50
	100	32	95 x 70	52/44.5 x 76/72	11	36	141	100		5387UAC100P52
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5387XSC100P50
	100	32	95 x 70	52/44.5 x 76/72	11	36	141	100		5387XSC100P52
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	100		5387UAC125P50
	125	32	95 x 70	52/44.5 x 76/72	11	38	165	100		5387UAC125P52
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	80		5387XSC125P50
	125	32	95 x 70	52/44.5 x 76/72	11	38	165	100		5387XSC125P52
	150	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	190	100		5387UAC150P50
	150	32	95 x 70	52/44.5 x 76/72	11	38	194	100		5387UAC150P52
Swivel Casters with directional lock										
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5381UAC100P50
	100	32	95 x 70	52/44.5 x 76/72	11	36	141	100		5381UAC100P52
	100	32	77 x 67	61,5/56 x 51,5/46,5	8,5	36	137	100		5381XSC100P50
	100	32	95 x 70	52/44.5 x 76/72	11	36	141	100		5381XSC100P52
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	100		5381UAC125P50
	125	32	95 x 70	52/44.5 x 76/72	11	38	165	100		5381UAC125P52
	125	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	161	80		5381XSC125P50
	125	32	95 x 70	52/44.5 x 76/72	11	38	165	100		5381XSC125P52
	150	32	77 x 67	61,5/56 x 51,5/46,5	8,5	38	190	100		5381UAC150P50
	150	32	95 x 70	52/44.5 x 76/72	11	38	194	100		5381UAC150P52



Wheel: UAC
Wheel center: Polyamide, Tread: Polyurethane, with integrated threadguards, precision ball bearing, stainless

Wheel: XSC electric conductive, non-marking
Wheel center: Polyamide, Tread: Polyurethane, with integrated threadguards, precision ball bearing, stainless

Grey brake pedal
These casters are available with grey locking lever.

LEVINA XL
In wheel diameter 125 mm these casters are also available with extended fork for a better access to the brake pedal.

80 - 100kg



Design Casters Series LEVINA stainless


Housing and wheels made from high grade synthetic materials with integrated threadguards, double ball bearing swivel head, all metal components stainless steel,

Color: silver-grey RAL 7001

Load capacity tested according EN 12530



	Wheel diameter [mm]	Tread width [mm]	Center hole [mm]			Offset [mm]	Overall height [mm]	Load capacity [kg]		Order number
Swivel Casters										
	100	32	11			36	137	100		5380UAC100P30-11
	100	32	13			36	137	100		5380UAC100P30-13
	100	32	11			36	137	100		5380XSC100P30-11
	100	32	13			36	137	100		5380XSC100P30-13
	125	32	11			38	161	100		5380UAC125P30-11
	125	32	13			38	161	100		5380UAC125P30-13
	125	32	11			38	161	80		5380XSC125P30-11
	125	32	13			38	161	80		5380XSC125P30-13
	150	32	11			38	190	100		5380UAC150P30-11
	150	32	13			38	190	100		5380UAC150P30-13
Swivel Casters with total lock										Order number
	100	32	11			36	137	100		5387UAC100P30-11
	100	32	13			36	137	100		5387UAC100P30-13
	100	32	11			36	137	100		5387XSC100P30-11
	100	32	13			36	137	100		5387XSC100P30-13
	125	32	11			38	161	100		5387UAC125P30-11
	125	32	13			38	161	100		5387UAC125P30-13
	125	32	11			38	161	80		5387XSC125P30-11
	125	32	13			38	161	80		5387XSC125P30-13
	150	32	11			38	190	100		5387UAC150P30-11
	150	32	13			38	190	100		5387UAC150P30-13
Swivel Casters with directional lock										Order number
	100	32	11			36	137	100		5381UAC100P30-11
	100	32	13			36	137	100		5381UAC100P30-13
	100	32	11			36	137	100		5381XSC100P30-11
	100	32	13			36	137	100		5381XSC100P30-13
	125	32	11			38	161	100		5381UAC125P30-11
	125	32	13			38	161	100		5381UAC125P30-13
	125	32	11			38	161	80		5381XSC125P30-11
	125	32	13			38	161	80		5381XSC125P30-13
	150	32	11			38	190	100		5381UAC150P30-11
	150	32	13			38	190	100		5381UAC150P30-13



Wheel: UAC
Wheel center: Polyamide, Tread: Polyurethane, with integrated threadguards, precision ball bearing, stainless

Wheel: XSC electric conductive, non-marking
Wheel center: Polyamide, Tread: Polyurethane, with integrated threadguards, precision ball bearing, stainless

Grey brake pedal
These casters are available with grey locking lever.

LEVINA XL
In wheel diameter 125 mm these casters are also available with extended fork for a better access to the brake pedal.



80 - 100kg



Design Casters Series LEVINA stainless

Housing and wheels made from high grade synthetic materials with integrated threadguards, metal components stainless steel, Color: silver-grey RAL 7001

Load capacity tested according EN 12530



	Wheel diameter [mm]	Tread width [mm]	Bolt-Ø [mm]	Bolt length [mm]	Offset [mm]	Overall height [mm]	Load capacity [kg]	Order number
Swivel Casters								
	100	32	22	45	36	137	100	5380UAC100R05-22
	100	32	25.4	45	36	137	100	5380UAC100R05-25.4
	100	32	28	45	36	137	100	5380UAC100R05-28x45
	100	32	25.4	45	36	137	100	5380XSC100R05-25.4
	100	32	28	45	36	137	100	5380XSC100R05-28x45
	125	32	25.4	45	38	161	100	5380UAC125R05-25.4
	125	32	28	45	38	161	100	5380UAC125R05-28x45
	125	32	25.4	45	38	161	80	5380XSC125R05-25.4
	125	32	28	45	38	161	80	5380XSC125R05-28x45
	150	32	28	45	38	190	100	5380UAC150R05-28x45
	150	32	25.4	45	38	190	100	5380UAC150R05-25.4
Swivel Casters with total lock								
	100	32	25.4	45	36	137	100	5387UAC100R05-25.4
	100	32	28	45	36	137	100	5387UAC100R05-28x45
	100	32	25.4	45	36	137	100	5387XSC100R05-25.4
	100	32	28	45	36	137	100	5387XSC100R05-28x45
	125	32	25.4	45	38	161	100	5387UAC125R05-25.4
	125	32	28	45	38	161	100	5387UAC125R05-28x45
	125	32	25.4	45	38	161	80	5387XSC125R05-25.4
	125	32	28	45	38	161	80	5387XSC125R05-28x45
	150	32	25.4	45	38	190	100	5387UAC150R05-25.4
	150	32	28	45	38	190	100	5387UAC150R05-28x45
Swivel Casters with directional lock								
	100	32	25.4	45	36	137	100	5381UAC100R05-25.4
	100	32	28	45	36	137	100	5381UAC100R05-28x45
	100	32	25.4	45	36	137	100	5381XSC100R05-25.4
	100	32	28	45	36	137	100	5381XSC100R05-28x45
	125	32	25.4	45	38	161	100	5381UAC125R05-25.4
	125	32	28	45	38	161	100	5381UAC125R05-28x45
	125	32	25.4	45	38	161	100	5381XSC125R05-25.4
	125	32	28	45	38	161	80	5381XSC125R05-28x45
	150	32	28	45	38	190	100	5381UAC150R05-28x45
	150	32	25.4	45	38	190	100	5381UAC150R05-25.4

All versions available with R05-22mm solid stem.

 <p>Wheel: UAC Wheel center: Polyamide, Tread: Polyurethane, with integrated threadguards, precision ball bearing, stainless</p>	 <p>Wheel: XSC electric conductive, non-marking Wheel center: Polyamide, Tread: Polyurethane, with integrated threadguards, precision ball bearing, stainless</p>	 <p>Grey brake pedal These casters are available with grey locking lever.</p>	 <p>LEVINA XL In wheel diameter 125 mm these casters are also available with extended fork for a better access to the brake pedal.</p>
--	---	---	--

80 - 100kg



Design Casters Series LEVINA stainless

Housing and wheels made from high grade synthetic materials, metal components stainless steel,
 Color: silver-grey RAL 7001
 Load capacity tested according EN 12530



Swivel Casters									Order number
	100	32	11			36	137	80	5380PJO100P30-11
	100	32	13			36	137	80	5380PJO100P30-13
	125	32	11			38	161	100	5380PJO125P30-11
	125	32	13			38	161	100	5380PJO125P30-13

Swivel Casters with total lock									Order number
	100	32	11			36	137	80	5387PJO100P30-11
	100	32	13			36	137	80	5387PJO100P30-13
	125	32	11			38	161	100	5387PJO125P30-11
	125	32	13			38	161	100	5387PJO125P30-13

Swivel Casters with directional lock									Order number
	100	32	11			36	137	80	5381PJO100P30-11
	100	32	13			36	137	80	5381PJO100P30-13
	125	32	11			38	161	100	5381PJO125P30-11
	125	32	13			38	161	100	5381PJO125P30-13

Wheel: PJO
 Wheel center: Polypropylene, Tread: TENTEprene (thermoplastic rubber), without threadguards, plain bearing

Small Threadguard
 These casters are available with PIP wheel and small threadguards for the food industry.

Grey brake pedal
 These casters are available with grey locking lever.